Energy & Store
Development Conference

E+SC

September 7-10, 2014 St. Louis Union Station Hotel St. Louis, MO









#### **Net Zero Store Update**

Jamie J. Meyers, LEED AP, Manager of Sustainability, Walgreens Rob Olden, CEM, Director of Engineering, North America, GI Energy

# 20% IRR over 5 years

120,000 kWh in refrigeration

14,820 SF of roof space

15/7/365

**Footprint** 

Precedence

**Brand Reputation** 







First Solar Project in 2008

Now have 150, with 200 more on the books

First LEED Project in 2009

Now in LEED Volume Program

First all LED store in 2010

All new stores receive an LED lighting package

## **Footprint**

8,215

120,000,000

28W to 25W

\$765/year/store

 $$765 \times 8,215 = $6,284,475$ 

#### **Precedence**

7,665 kwh 41,000,000 kWh 46,300 kwh 138,000,000 kWh 37,000 kwh 148,000,000 kWh

### **Brand Reputation**

# Tolalgreeus. AT THE CORNER OF HAPPY & HEALTHY®

"Everyday I help people get, stay, and live well."

1. Energy Produced – Energy Consumed > 0

2. Operate like a normal Walgreens

3. Share our learnings


# Close proximity to corporate office

A cooperative developer

A supportive community


**Correct timeframe** 





# 0 - 425,000 kwh > 0





325,000 kwh




- "Always on renewable"
- 30-50% carbon reduction
- Demand reduction (0.65 kW/ton)
- Significant LCC reduction
- Net Zero ready!










0 - 425,000 kwh > 0



325,000 kwh – 340,000 kwh > 0






300,000 kwh







0 - 425,000 kwh > 0




325,000 kwh - 340,000 kwh > 0




300,000 kwh - 315,000 kwh > 0





275,000 kwh





# 0 - 425,000 kwh > 0



325,000 kwh - 340,000 kwh > 0




300,000 kwh - 315,000 kwh > 0




275,000 kwh - 260,000 kwh > 0







CHICAGO AVENUE



WEST ELEVATION - CHICAGO AVE.







# 0 - 425,000 kwh > 0



325,000 kwh - 340,000 kwh > 0



300,000 kwh - 315,000 kwh > 0




275,000 kwh - 260,000 kwh > 0




256,000 kwh - 250,000 kwh > 0









## 0 - 425,000 kwh > 0



325,000 kwh - 340,000 kwh > 0



300,000 kwh - 315,000 kwh > 0



275,000 kwh - 260,000 kwh > 0



256,000 kwh - 250,000 kwh > 0




220,000 kwh - 200,000 kwh > 0

















## CO2 REFRIGERATION: LESSONS LEARNED

#### **Benefits of Geothermal**



#### May 8: Case in Point


Geothermal loop provides steady condensing temperatures < 15C (60F)




Blue= Transcritical Op. (72 BAR)
Orange= PT1

Pink= OA Temp Navy= GEOTemp<sub>out</sub> Green=GEOTemp<sub>in</sub> Red= GEO power


#### **Hybrid Geothermal Concept**



## "Typical" Hybrid Geothermal Design




## **CO2 Central Plant Design**




#### Net Zero, explained

- T − 1 year... and counting
- It's actually a continual process
  - Collect data
  - Diagnose
  - Corrective actions







#### **Total Net Meter Data**




#### **Gross Energy Consumption**




#### **CO2 Heat Pump Data**




## **Heating Operation: Expected**



#### **Heating Operation: Actual**




### **Heating Loads**






### **Cooling Operation: Expected**




## **Cooling Operation: Actual**




#### **HT (Heat Pump Compressor)**

Instantaneous HT COPs up to 10, range:4-6 Aggregate hydronic COP = 3.4



#### **MT/LT Compressor Power**


8% energy penalty Solution: right-size the compressors



AVG = 5.4kWEXP = 5.0 kW

#### System Impact of the Gas Cooler


- —GC Machine TT2 Gas Cooler Out Temperature °F —Geo Loop Well Field Leaving Temperature (BTU-01) °F
- ——Geo Loop Well Field Entering Temperature (BTU-01) °F ——Geo Loop Flow (BTU-01) GPM
- —Outdoor Air Temperature °F GC Machine S1 Gas Cooler Output Signal %



August 22: Gas Cooler Working

August 23: Gas Cooler Tripped

#### **Geothermal Energy Data**



#### **Coarse Tuning = Course Corrections**

- Oversizing of MT/LT Compressor is having a significant impact
- The gas cooler is offline and has been all summer
- More heat rejection into the store is required during the winter
- Acoustic design must be addressed to enable full airflow and maximum DT

#### **Service Issues**

- CO2 is less expensive than synthetic refrigerants!
- 2-3 leaks that were caught and addressed without loss of stock.
  - Gas Cooler Braze failed
  - Service caps have failed
  - Ball valve on carbon steel line
- Manual resets are completely unnecessary when the system is fully remote controlled
  - Gas cooler
  - Compressor lock out
- Triple temp racks are sensitive to % charge.

#### **Overall Lessons Learned**

- UL Certification hurdles. 5x pressure rating is challenging at 90 Bar
- Incorporating HVAC into refrigeration rack breaks down historic barrier to innovation
- Geothermal loop adds redundancy and increases operational flexibility
- Aluminum piping is a no-brainer
- US suppliers lack sufficient stock of 80 Bar rated components.
- Real time monitoring and transparency are vital

#### **Overall Lessons Learned**

- Don't Rush!
- Commissioning before opening
- Engage all contractors early
- Punchlist
- Don't do this project before historically cold winters